

Conundrum Holdings Pty Ltd

MATERIAL SAFETY DATA SHEET

Quarry and Sand Products

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Quarry and Sand Products
Other Names: Crushed Rock, Road Base, Crushed Concrete, Aggregate, Blue Metal, Rail Ballast, Rip Rap, Beaching Material, Fill, Quarry Dust, Quartz Sand, Concrete Sand
Recommended Use: Quarry and sand products are used in building and construction projects including road making, rail ballast and concrete.
Company: Conundrum Holdings Pty Ltd
ABN 39 007 076 020
Address: PO Box 100, Kilmore, VIC 3764
Telephone: 03 5781 0103 (7:30am to 5:00pm Mon to Fri only)
Facsimile: 03 5782 0188 (7:30am to 5:00pm Mon to Fri only)
Emergency Phone Number: Poisons Information Centre 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

HAZARDOUS SUBSTANCE NON-DANGEROUS GOODS

This product contains crystalline silica. Crystalline silica dust is classified as **Hazardous** according to the criteria of the Australian Safety and Compensation Council ASCC (formerly NOHSC) (Approved Criteria for Classifying Hazardous Substances [NOHSC:1008] 3rd Edition).

- The solid product as supplied is classified as non-hazardous.
- Dust in/on the supplied product or created when the product is cut, drilled, abraded or crushed may contain crystalline silica some of which may be respirable (small enough to reach deep into the lungs when breathed in).

Risk Phrases: **R20:** Harmful by inhalation (applies to dust)
R48: Danger of serious damage to health by prolonged exposure through inhalation (applies to dust)

Safety Phrases: **S22:** Do not breathe dust

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:	Proportion (w/w):	CAS Number:
Crystalline Silica (SiO₂)	see below	14808-60-7
Basalt (Northern Quarries)	up to 0.2%	
Hornfels (Stawell Quarry)	up to 74%	
Quartzite (McKenzie Creek Quarry)	up to 98%	
Quartz Sand (Jeparit Sand)	up to 99%	


Other Ingredients determined not to be hazardous (balance) Not required

- Stabilized crushed rocks are made by blending quarry materials with up to 4% Portland Cement (CAS Number 65997-15-1).
- Some material sold as quarry products are made from recycled by-products from building/pavement demolition and wash out waste from concrete operations. These products do not contain asbestos.
- Depending on the source materials, the Crystalline Silica content of any particular quarry product can range from 0 to 100%

Date issued: 4 May 2007
Issue number: 4
Authorised by: Tom Kerr
Date printed: 13 Feb 2009

Previous issue date: 2 May 2007

Date of first issue: 1 Jan 1999
Max review interval: 5 years
Manual index location: 4.vi
Form: 0203



Conundrum Holdings Pty Ltd

MATERIAL SAFETY DATA SHEET

Quarry and Sand Products

SECTION 4: FIRST AID MEASURES

- Swallowed:** Rinse mouth and lips with water. Do not induce vomiting. If symptoms persist, seek medical attention.
- Eye:** Flush thoroughly with flowing water, while holding eyelids open. If symptoms such as irritation or redness persist, seek medical attention.
- Skin:** Remove heavily contaminated clothing. Wash off skin thoroughly with water. Use a mild soap if available. Shower if necessary. Seek medical attention for persistent irritation of the skin.
- Inhaled:** Remove to fresh air, away from dusty area. If respiratory irritation occurs, seek immediate medical attention.
- First Aid Facilities:** Eye wash station and normal wash-room facilities.
- Advice to Doctor:** Treat symptomatically

SECTION 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable or combustible
- Hazards from combustion products:** None
- Suitable extinguishing media:** Not applicable
- Special protective precautions and equipment for fire fighters:** None

SECTION 6: ACCIDENTAL RELEASE MEASURES

- Spills:** Dust is best cleaned up by vacuum device to avoid making dust airborne. If spillage is to be swept or shoveled into containers, it should be wetted down with water to reduce dust generation.
- Recommendations on exposure control and personal protection should be followed during spill clean-up.

SECTION 7: HANDLING AND STORAGE

- Handling:** Avoid breathing dust. Respirable dusts can be generated during processing, handling and storage. Use control measures such as ventilation, enclosure of materials, covered loads on trucks, and wetting down material while in use.
- Storage:** When stockpiling and handling large quantities of quarry or sand products, care should be taken to avoid steep faces on the stockpile, which can fall without warning.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION


- Exposure Standards:** **Australian Safety and Compensation Council (ASCC) (formerly NOHSC) National Occupational Exposure Standard (NES)**
- Crystalline Silica (Quartz): 0.1 mg/m³ time weighted average (TWA) as respirable dust
- Total dust (of any type, or particle size): 10 mg/m³ TWA
- Dust must be kept to a minimum to ensure respirable dust level remains below NES**
- Engineering Controls:** Avoid generating dust. Any activities which may generate dust must be performed in a well ventilated space. Mechanical ventilation or local exhaust ventilation must be used if levels of respirable dust approach the NES. If dust generation cannot be avoided, personal respiratory protection is required.

Date issued: 4 May 2007
Issue number: 4
Authorised by: Tom Kerr
Date printed: 13 Feb 2009

Previous issue date: 2 May 2007

Page 2 of 5

Date of first issue: 1 Jan 1999
Max review interval: 5 years
Manual index location: 4.vi
Form: 0203



Conundrum Holdings Pty Ltd

MATERIAL SAFETY DATA SHEET

Quarry and Sand Products

Personal Protective Equipment:


- Skin:** Ensure a high level of personal hygiene is maintained when using this product. That is; always wash hands before eating, drinking, smoking or using the toilet.
Wear loose comfortable clothing and gloves (standard duty leather or equivalent compliant to AS/NZS 2161). Remove all contaminated clothing. Wash clothes regularly and separate from other clothes. Do not contaminate the home environment with dusty work clothes and shoes. Do not shake out work clothes before laundering.
- Eyes:** Safety goggles or spectacles (compliant to AS/NZS 1337) should be worn if exposed to dust.
- Respiratory:** Where engineering and handling controls are not enough to minimize exposure to total dust and to respirable crystalline silica, personal respiratory protection must be worn. Respiratory protection used must conform to AS/NZS 1716 and be used in accordance with AS/NZS 1715. An approved particulate "dust mask", either class P1 or P2, may provide the required minimum protection factor for the ambient dust level in most cases. Where high levels of dust are encountered, more efficient cartridge-type or powered respirators or supplied-air helmets may be necessary. Use only respirators that bear the Australian Standards mark and are fitted and maintained accordingly.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

- Appearance:** Colour range: white/grey to dark blue/grey
Size range: greater than 100mm to dust/sand
- Odour:** Normally no odour
- pH:** 4.0 – 10.8
- Vapour Pressure:** Not determined
- Vapour Pressure:** Not determined
- Boiling Point/Range:** Not determined
- Freezing/Melting Point:** Not determined
- Solubility:** Insoluble
- Density:** 2.5 - 2.7 t/m³
- Flash Point:** Not applicable
- Flammability Limits:** Not applicable
- Ignition Temperature:** Not applicable
- Particle Size:** A *proportion* of the dust may be respirable (below 10µm) and if it becomes airborne constitutes an exposure if inhaled

SECTION 10: STABILITY AND REACTIVITY

- Chemical Stability:** Chemically stable
- Conditions to Avoid:** Dust generation
- Incompatible Materials:** None
- Hazardous Decomposition Products:** None
- Hazardous Reactions:** None



Conundrum Holdings Pty Ltd

MATERIAL SAFETY DATA SHEET

Quarry and Sand Products

SECTION 11: TOXICOLOGICAL INFORMATION

Health Effects:

Short Term (Acute) Exposure:

Swallowed: Unlikely to occur under normal conditions of use. Swallowing of dust may cause abdominal discomfort.

Eyes: Dust is irritating to the eyes, causing watering and redness. Exposure to dust may aggravate pre-existing eye conditions.

Skin: Dust may be mildly irritating and abrasive to the skin due to its physical properties.

Inhaled: Dust is mildly irritating to the nose, throat and lungs, resulting in coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

Long Term (Chronic) Exposure:

Eyes: Dust may cause irritation and inflammation of the eyes and aggravate pre-existing eye conditions.

Skin: Repeated heavy contact with dust may cause drying of the skin and can result in a rash (irritant contact dermatitis) typically affecting the hands. Over time this may become chronic and can also become infected.

Inhaled: Repeated exposure to dust may result in increased nasal and respiratory secretions and coughing. High level exposures can increase the risk of bronchitis and pneumonia. Repeated inhalation of dust containing crystalline silica may result in an irreversible pulmonary fibrosis (scarring of the lung) termed silicosis, including acute or accelerated silicosis. Secondary infections such as bronchitis and tuberculosis are often associated with silicosis. It may also increase the risk of scleroderma (a disease affecting the skin, joints, blood vessels and internal organs) and other auto-immune disorders. Tobacco smoking is considered to increase the adverse effects of exposure to dust, including crystalline silica.

ASCC has not classified crystalline silica as a carcinogen. The most current research indicates no excess risk of lung cancer or other cancers from using these products.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Quarry products pose no ecological risk. They are non-toxic to aquatic and terrestrial organisms and are biodegradable.

Persistence and

Degradability: Quarry products are persistent and are non-degradable.

Mobility: Low mobility would be expected in a landfill situation.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal: Quarry and sand products can be treated as a common waste for disposal or dumped into a landfill site in accordance with local authority guidelines. Measures should be taken to avoid dust generation during disposal and exposure and personal precautions should be observed (see above).

SECTION 14: TRANSPORT INFORMATION

UN Number: None allocated

UN Proper Shipping Name: None allocated

Class and Subsidiary Risk: None allocated

Packing Group: None allocated

Date issued: 4 May 2007

Previous issue date: 2 May 2007

Date of first issue: 1 Jan 1999

Issue number: 4

Max review interval: 5 years


Authorised by: Tom Kerr

Manual index location: 4.vi

Date printed: 13 Feb 2009

Page 4 of 5

Form: 0203



Conundrum Holdings Pty Ltd

MATERIAL SAFETY DATA SHEET

Quarry and Sand Products

Special Precautions for User: See above
HAZCHEM Code: None allocated

SECTION 15: REGULATORY INFORMATION

- Crystalline silica dust is classified as **Hazardous** according to the criteria of the Australian Safety and Compensation Council ASCC (formerly NOHSC) (Approved Criteria for Classifying Hazardous Substances [NOHSC:1008] 3rd Edition).
- Persons who have potential for exposure above the NES may be required by Regulations to have periodic health surveillance including Chest X-ray (see Occupational Health and Safety (Hazardous Substances) Regulations (Victoria) 1999 or other relevant local State Government Regulations).

SECTION 16: OTHER INFORMATION

- Smoking and other airborne particles: Inhalation of airborne particles from other sources of work, as well as those from tobacco smoking increases the risk of occupational respiratory diseases. It is recommended that all storage and work areas should be smoke-free zones and that other airborne contaminants are kept to a minimum.

References:

Australian Standards:

AS/NZS 1337: Eye Protectors For Industrial Applications

AS/NZS 1715: Selection, Use and Maintenance of Respiratory Protective Devices

AS/NZS 1716: Respiratory Protective Devices

AS/NZS 2161: Occupational Protective Gloves

Other:

National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition [NOHSC:2011 (2003)], April 2003, National Occupational Health and Safety Commission

Approved Criteria for Classifying Hazardous Substances 3rd Edition [NOHSC:1008(1999)], 1999, National Occupational Health and Safety Commission

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)], 1995, National Occupational Health and Safety Commission

Occupational Health and Safety (Hazardous Substances) Regulations (Victoria) 1999

NOTICE: At the date of publication the information contained in this Material Safety Data Sheet is, to the best of our knowledge, accurate and is given in good faith but no warranty expressed or implied is made. The suggested procedures are not necessarily all inclusive nor fully adequate for all circumstances in which the product may be used. Users are advised to make their own determination as to the suitability of the information in relation to their particular purposes and specific circumstances. We accept no responsibility for any resultant loss or damage as a result of any person acting or refraining from action as a result of the information provided in this document as it may be applied under conditions beyond our control. Where the information provided discloses a potential hazard or hazardous ingredient, adequate warning should be provided to employees and users and appropriate precautions taken to ensure safe systems of work are in place.

END OF MSDS

Date issued: 4 May 2007
Issue number: 4
Authorised by: Tom Kerr
Date printed: 13 Feb 2009

Previous issue date: 2 May 2007

Page 5 of 5

Date of first issue: 1 Jan 1999
Max review interval: 5 years
Manual index location: 4.vi
Form: 0203